## **About EOS**

Electrical Oil Services (EOS) is a key brand of HCS Group GmbH and a leading supplier of both regenerated and unused electrical insulating oils and associated services in Europe. EOS specialists have 60 years' experience in the production and marketing of insulating oils and supply both large and small customers in the electricity distribution industry with tailor-made solutions.



## **Electrical Oil Services**

www.electricaloilservices.com

Haltermann Carless UK Bridges Road, Ellesmere Port Cheshire CH65 4EQ Great Britain +44 (0)845 602 1003 EOS@h-c-s-group.com Electrical Oil Services GmbH
Oehleckerring 6a
22419 Hamburg
Germany
+49 (0) 40 500 910 850
sales@electricaloilservices.com

The product information contained in this brochure has been compiled to the best of our knowledge on the basis of thorough tests and research work and with regard to the current state of our practical experience in the industry. This product information is non-binding. Our statements relating to possible uses of the product do not constitute a guarantee that such uses are appropriate in a particular user's case or that such uses do not infringe the patents or proprietary rights of any third party. We assume no risk or liability whatever in connection with any particular use, if not expressly confirmed by us in writing. Therefore HCS Group and its affiliated companies grant no warranty and does not accept any liability in connection with this product information or its use. Except where noted otherwise, all registered trademarks are owned by HCS Group or its affiliated companies. The reproduction of any or all of the information contained in this brochure is expressly forbidden without HCS's prior written consent.





## EOS® Premium Regenerated Insulating Oil as sustainable as sustainable solution for transformers and switchgears.

- EOS® Premium und EOS® Premium X (inhibited) Regenerated insulating oil according to highest quality standard
- Ecologically-sound and sustainable alternative compared to new insulating oil
- ◆ "As new" properties meets the performance requirements of IEC 60296
- Available with or without inhibitor
- Price stable: not subject to market price fluctuations
- Secure supply; independent of external market influences



## Let's save valuable resources - together

Customers from the electricity supply industry have appreciated us as a reliable partner for many decades. We are continuously working on the further development of our products and comprehensive services to meet the individual needs of our customers.

To conserve natural resources, our EOS® Premium product uses carefully selected used insulating oils to produce a sustainable alternative to unused (new) insulating oil. This product development demonstrates our commitment to the electricity industry, safeguarding valuable resources today, tomorrow and for years to come.

Specifications for EOS* Premium Regenerated Insulating Oil (IEC 60296)	
Water content [mg/kg]	< 30 (typically < 10)
Breakdown voltage [kV]	> 30 (typically > 60)
Acidity [mgKOH/g]	< 0.01
Oxidation stability @ 120 °C at 164h	< 1.2 mgKOH/g total acidity < 0.8 % sludge
PCB content [mg/kg]	Non-detectable
DBDS	Non-detectable
Furfural content [mg/kg]	< 0.05